

BNC Male Cable with Molded Strain Relief



Rating: Maximum voltage for *hands free use*: 500 Vrms*, +122°F (+50°C) max., ("Y" Cable 176°F (+80°C).)

BNC: *Body*: tarnish resistant nickel-plated brass; *Center Contact*: gold-plated brass; *Dielectric*: PTFE.

Strain Relief: PVC molded directly to cable and connectors.

See chart on page 7 for additional wire and cable specifications.

Length	50Ω Cable O.D. .195in (4.95mm) RG58C/U	50Ω Cable O.D. .206in (5.23mm) RG223	75Ω Cable O.D. .242in (6.15mm) RG59B/U	50Ω Cable O.D. .100in (2.54mm) RG174/U	50Ω Cable O.D. .195in 4.95mm) RG58C/U
.5ft (0.2m)	2249-C-6	—	2249-E-6	2249-K-6	—
1ft (0.3m)	2249-C-12	2249-Y-12	2249-E-12	2249-K-12	—
2ft (0.6m)	2249-C-24	2249-Y-24	2249-E-24	2249-K-24	—
3ft (0.9m)	2249-C-36	2249-Y-36	2249-E-36	2249-K-36	—
4ft (1.2m)	2249-C-48	2249-Y-48	2249-E-48	2249-K-48	—
5ft (1.5m)	2249-C-60	2249-Y-60	2249-E-60	2249-K-60	5266-C-60
6ft (1.8m)	2249-C-72	2249-Y-72	2249-E-72	2249-K-72	—
8ft (2.4m)	2249-C-96	2249-Y-96	—	2249-K-96	—
10ft (3.0m)	2249-C-120	2249-Y-120	2249-E-120	2249-K-120	—
12ft (3.7m)	2249-C-144	2249-Y-144	2249-E-144	—	—
15ft (4.6m)	2249-C-180	2249-Y-180	2249-E-180	2249-K-180	—
20ft (6.1m)	2249-C-240	2249-Y-240	2249-E-240	2249-K-240	—
25ft (7.6m)	2249-C-300	—	2249-E-300	2249-K-300	—
30ft (9.1m)	2249-C-360	—	2249-E-360	—	—
50ft (15.2m)	2249-C-600	—	2249-E-600	—	—

Model 2249-C is Pomona Electronics' most popular cable. The 50Ω RG58C/U cable makes it ideal for most test and measurement applications.

Model 2249-Y is a 50Ω RG223/U cable with double shield. Use when additional shielding is required.

Model 2249-E RG59B/U is a 75Ω cable, making it the right choice for use with TV, video and LAN applications.

Model 2249-K RG174/U offers superior flexibility in a 50Ω cable.

Model 5266-C is the same high quality construction as Model 2249-C with a connector on **(one end only.)**