

TECHNICAL DATA

Fluke 930 Non-Contact Tachometer



Key features

- 6-digit backlight display reads the data clearly
- Signal detection reminder avoids invalid detection actions
- Maximum/minimum/average value and final readings
- Setting/Turning off the automatic power-off function
- Small size and easy to hold
- 1-year warranty

Product overview: Fluke 930 Non-Contact Tachometer

Fluke 930 is a handheld tachometer and is equivalent to a Fluke 931 with minimum configuration and can accurately measure the revolutions per minute (RPM) or surface speed and distance. With only the non-contact measuring function provided, it's more affordable and offers consistent quality.

Applications:

- Heavy manufacturing environments, e.g. automotive, textile, pulp and paper, metalwork
- Water purification plants
- Machining and chemical manufacturing plants
- HVAC compressors for industrial systems



Specifications: Fluke 930 Non-Contact Tachometer

Rotation speed measurement	
Range	Optical (non-contact) measurement: 1 to 99999 revolutions/minute Contact measurement: 1 to 19999 revolutions/minute (Fluke 931 only)
Precision	±0.02%RD+1
Sensing distance	(optical) 500 mm
Specifications	
Battery type	(2) 1.5V LR6 (alkaline) AA battery
Battery life	About 40 hours
Operating temperature	0°C to 50°C
Storage temperature	-20°C to 70°C
Weight	250 g
Dimensions	175 × 60 × 28 mm
Warranty period	1 year

Ordering information



Fluke-930 (CN)

Fluke 930 Non-Contact Tachometer

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa +31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

Fluke Electronics (Malaysia) Sdn Bhd

Suite D-3A-4, Block D

SouthGage Commercial Centre, No2

Jalan Dua Off Jln Chan Sow Lin

55200 KL

Malaysia

Email: info.asean@fluke.com

www.fluke.com/my

©2025 Fluke Corporation. Specifications subject to change without notice.

12/2025

Modification of this document is not permitted without written permission from Fluke Corporation.