

TECHNICAL DATA

AC288 Terminal Block Probe with Retractable Probe Tip



Key features

- Retractable probe tip designed for increased safety, while providing flexibility to reach deep connection points
- Recommended for use with TL224, TL222 or TL221 Test Leads
- 11.5 cm (4.5 in) insulated, flexible shaft
- 1 mm diameter probe tip extends out to 8.4 mm (0.33 in) length
- Retractable probe tip is made with stainless steel
- Safety rated: IEC 61010-031, CAT III 1000 V, CAT IV 600 V
- Operating temperature: -20 °C to 55 °C (-4 °F to 131 °F), 90% RH
- One-year warranty

Product overview: AC288 Terminal Block Probe with Retractable Probe Tip

Use for safe and secure connections to clamp and screw type terminal blocks.

Ordering information



AC288

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa +31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

Fluke Electronics (Malaysia) Sdn Bhd

Suite D-3A-4, Block D

SouthGage Commercial Centre, No2

Jalan Dua Off Jln Chan Sow Lin

55200 KL

Malaysia

Email: info.asean@fluke.com

www.fluke.com/my

©2025 Fluke Corporation. Specifications subject to change without notice.

12/2025

Modification of this document is not permitted without written permission from Fluke Corporation.