


Model 3560, 3562, 3564, 4690 Banana Jack to #12, 16, 20 & 22 Pin Socket



Features

- Ideal test adapters for rapid testing of the hard-to-get to pins of multi-pin connectors.
- Flexible tip allows testing of adjacent contacts.
- Full insulation protects against shorting or contact damage.
- Model 4690 will also slip over 0.025" (0.63mm)

Materials

Insulation: Polyvinyl Chloride (PVC)
Banana Jack Body (upper connector)

Material: Brass.

Finish: Bright Tin Plated

Socket (lower connector)

Material: Copper Alloy

Finish: Gold Plated over Copper Plating

Ordering Information

Model: 3560-*, 3562-*, 3564-*, 4690-*

* = Color: -0 Black, -2 Red

Ordering Example: 3560-2 (red adapter)

Model	Contact Size	Type	Current
4690	22 AWG .030" (.76mm)	Socket	3 Amps
3560	20 AWG .040" (1.02mm)	Socket	
3562	16 AWG .063" (1.60mm)	Socket	
3564	12 AWG .093" (2.36mm)	Socket	
Voltage Rating: For CE Compliance and for personal safety, do not hold in hand when voltages exceed 33 Vrms/70 Vdc. Maximum voltage for hands free use: 2500 Vrms Max. Operating Temperature: +55°C (+131°F) Max.			