

TECHNICAL DATA

Fluke 6200-2 Portable Appliance Testers



Key features

Fluke Simplifies Portable Appliance Testing

- Dedicated key for each test for 'one-touch' testing
- Complies with the new standards BS EN 50678 and BS EN 50699
- Pre-set pass/fail levels to save time
- Large backlit display for easy reading
- Single mains socket for appliance connection
- Separate IEC socket for easy mains/extension lead testing
- Detachable test leads for quick field replacement
- Integral carrying handle
- USB port for data transfer

Product overview: Fluke 6200-2 Portable Appliance Testers

Perform More Tests Each Day

The Fluke 6200-2 PAT tester is a low weight, small size, one-touch solution with redesigned auto-test capabilities to help you increase the number of portable appliance tests completed each day. The 6200-2 is designed to enable you to work faster without compromising safety – yours or your customer's.

One-Touch Solution...

Pre-set test routines are initiated from a single button. This not only simplifies testing but also facilitates a faster, more efficient way of working.

Low Weight...

Weighing approximately 3 kg, the 6200-2 is lightweight and easy to carry when working on-site. The hard rugged carrying case (supplied) not only offers protection during transit but also includes extra storage space for accessories and other tools.

Small Size...

This portable appliance testers is also extremely compact, and has Fluke's traditional ruggedness to be able to withstand working in the field. Packed with all the features you need for testing portable appliances, a Fluke PAT tester is a complete all-in-one solution.

Specifications: Fluke 6200-2 Portable Appliance Testers

Specifications		
Test specifications	The accuracy specification for the display range is defined as $\pm(\% \text{reading} + \text{digit counts})$ at 23 °C ± 5 °C, $\leq 75\%$ RH.	
	Between 0 °C and 18 °C and between 28 °C and 40 °C, accuracy specifications may degrade by 0.1 x (accuracy specification) per °C.	
	The measurement range meets the service operating errors specified in EN61557-1: 1997, EN61557-2: 1997, EN61557-4: 1997, EN61557-6: 1997, DIN VDE0404-2.	
Power-on test	The test indicates reversed L-N, missing PE, and measures the mains voltage and frequency.	
	Display range	90 V to 264 V
	Accuracy at 50 Hz	$\pm(2\% + 3 \text{ counts})$
	Resolution	1 V
	Input impedance	$> 1 \text{ M}\Omega // 2.2 \text{ nF}$
	Maximum input mains voltage	264 V
Earth bond test (R _{pe})	Display Range	0 to 19.99 Ω
	Accuracy (after bond test zeroing)	$\pm(2.5\% + 4 \text{ counts})$
	Resolution	0.01 Ω
	Test current	200 mA AC -0% +40% into 1.99 Ω 25 A AC $\pm 20\%$ into 25 m Ω at 230 V
	Open circuit voltage	$> 4 \text{ V AC}, < 24 \text{ V AC}$
	Bond test zeroing	can subtract up to 1.99 Ω

Insulation test (R iso)	Display range	0 to 299 MΩ
	Accuracy	±(5% + 2 counts) from 0.1 to 300 MΩ
	Resolution	0.01 MΩ (0 to 19.99 MΩ) 0.1 MΩ (20 to 199.9 MΩ) 1 MΩ (200 to 299 MΩ)
	Test voltage	500 V DC -0% + 10% at 500 kΩ load
	Test current	> 1 mA at 500 kΩ load, < 15 mA at 0 Ω
	Auto discharge time	< 0.5 s for 1 μF
	Max. capacitive load	Operational up to 1 μF
Touch current test	Display range	0 to 1.99 mA AC
	Accuracy	±(4% + 2 counts)
	Resolution	0.01 mA
	Internal resistance (via probe)	2 kΩ
	Measuring method	Probe*
Substitute leakage current test	Display range	0 to 19.99 mA AC
	Accuracy	±(2.5% + 3 counts)
	Resolution	0.01 mA
	Test Voltage	100 V AC ±20%
Load/leakage test: load current	Display range	0 A to 13 A
	Accuracy	±(4% + 2 counts)
	Resolution	0.1 A*
Load/leakage test: load power	Display range 230 V Mains	0.0 VA to 3.2 kVA
	Accuracy	±(5% + 3 counts)
	Resolution	1 VA (0 to 999 VA), 0.1 kVA (>1.0 kVA)*
Load/leakage test: leakage current	Display range	0 to 19.99 mA
	Accuracy	±(4% + 4 counts)
	Resolution	0.01 mA*
PELV test	Accuracy at 50 Hz	±(2% + 3 counts)
	Overload protection	300 V rms
	Warning threshold	25 V rms
*The appliance under test is energized at mains potential.		
Environmental specifications		
Operating temperature		0 to 40 °C
Relative humidity	Non condensing <10 °C	
	95% from 10 to 30 °C	
	75% from 30 to 40 °C	

Safety specifications			
Safety rating	Complies with EN61010-1 3rd edition		
	CAT II, 300 V, pol 2		
Mechanical and general specifications			
Size (L x W x H)		200 x 275 x 114 mm	
Weight		3.13 kg	
Power supply		230 V +10% -15%, 50 Hz ±2	
Power consumption (tester)		13 W typical (idle) 60 W max. during 25A Bond test	
Storage	Temperature	-10 to 60 °C	
	Corrosion	70 °C @ 95% RH for 5 days max.	
Operating altitude		0 up to 2000 m	
Sealing		IP-40 (enclosure), IP-20 (connectors)	
EMC		Complies with EN61326-1, portable	
EMI Immunity		3 V/m	

Ordering information



Fluke 6200-2

Fluke 6200-2 Portable Appliance Tester

- Fluke 6200-2 Portable Appliance Tester
- Quick reference guide
- Hard carrying case
- Test lead
- Test probe
- Crocodile clip
- Mains cord

Fluke. *Keeping your world up and running.®*

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com/en-gb

©2025 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
12/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**