

TECHNICAL DATA

PLS RBP5 SINGLE PACK



CE

Key features

- Rechargeable battery only
- Delivers 3x the operating time for your PLS laser level* (table in overview)
- Eliminate the need to buy alkaline batteries
- Compatible with PLS hand held lasers (3R, 3G, 5R, 5G, 6R, 6G, 180R, 180G)

Product overview: PLS RBP5 SINGLE PACK

*Battery life comparison guide with RBP5

Laser level	AA batteries	PLS RBP5
PLS 3R	≥ 30 hours	≥ 100 hours
PLS 3G	≥ 16 hours	≥ 45 hours
PLS 5R	≥ 20 hours	≥ 70 hours
PLS 5G	≥ 9 hours	≥ 25 hours
PLS 6R	≥ 8 hours	≥ 30 hours
PLS 6G	≥ 3 hours	≥ 12 hours
PLS 180R	≥ 8 hours	≥ 30 hours
PLS 180G	≥ 3 hours	≥ 12 hours

Maximize your laser level operating time up to 3x and eliminate alkaline battery purchases with the PLS RBP5

Rechargeable Battery Pack. The RBP5 is compatible with our newest point, line and combination laser levels; PLS 3G, 3R, 5G, 5R, 6G, 6R, 180G, 180R. Prevent jobsite downtime due to battery drain with the PLS RBP5 and avoid having to purchase extra batteries. The PLS RBP5 SINGLE PACK is a standalone accessory sold separately that comes with only the rechargeable battery.

PLS RBP5 SINGLE PACK features:

- Composition: Lithium-ion
- Voltage: 3.6 V
- Capacity: 5200 mAh

Specifications: PLS RBP5 SINGLE PACK

Battery	
Battery Type	Lithium-ion
Operating Time (estimated)	12 to 100 hours
Charging Time	6 to 8 hours
Temperature	
Operating	-10 °C to 50 °C (14 °F to 122 °F)
Storage	-20 °C to 50 °C (-4 °F to 122 °F)
Battery charging	0 °C to 45 °C (32 °F to 113 °F)
Compatibility	PLS 3R, 3G, 5R, 5G, 6R, 6G, 180R, 180G
Altitude	
Operating	2000 m
Storage	12,000 m
Size (H x W x L)	106 mm x 64 mm x 30 mm (4.2 in x 2.5 in x 1.2 in)
Weight	165 g (5.8 oz)
Electromagnetic compatibility (EMC)	
International	IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class A Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class A: Equipment is suitable for use in all establishments other than domestic and those directly connected to a low-voltage power supply network that supplies buildings used for domestic purposes. There may be potential difficulties in ensuring electromagnetic compatibility in other environments due to conducted and radiated disturbances.
Korea (KCC)	Class A Equipment (Industrial Broadcasting & Communication Equipment)
USA (FCC)	47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.

Ordering information



PLS RBP5 SINGLE PACK

PLS RBP5 SINGLE PACK

Includes:

- Li-ion Battery
-

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2025 Fluke Corporation.
Specifications subject to change without notice.
12/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**